

**Claims:**

1. A highchair in which a seat having a back-rest is carried by respective front and rear leg-supports, wherein the seat, its back and the front leg-support are provided together in one by an elongate, unitary member.
2. A highchair according to Claim 1 wherein the elongate member is a one-piece moulding.
3. A highchair according to Claim 2 wherein the one-piece moulding is a laminate.
4. A highchair according to Claim 3 wherein the laminate has a core of wood, plastics or a material of honeycomb structure.
5. A highchair according to Claim 4 wherein the laminate is faced with a wood veneer or plastics.
6. A highchair according to any one of Claims 1 to 5 wherein the rear-leg support is pivoted to the elongate member so that the highchair can be collapsed with the rear leg-support folded onto the front leg-support.
7. A highchair according to Claim 6 wherein the rear leg-support comprises a pair of legs.
8. A highchair according to Claim 7 wherein the legs are pivoted to the underside of the seat-portion of the elongate member.
9. A highchair according to any one of Claims 6 to 8 wherein a stay-element that is pivoted to the rear leg-support is selectively engageable within a socket on the underside of the seat-portion of the elongate member for

holding the rear leg-support extended rearwardly of the seat-portion in the erect condition of the highchair.

10. A highchair according to Claim 9 wherein the rear leg-support comprises a pair of interconnected, tubular legs and the stay-element is a tubular frame located between the legs and pivoted to them.

11. A highchair according to any one of Claims 1 to 10 wherein a tubular element that is attached to the underside of the seat-portion of the elongate member extends upwardly either side of the seat-portion to provide arm rests to the seat.

12. A highchair according to Claim 11 wherein a forwardly-extending tray is attached to the tubular element by mounts that engage releasably with the tubular element either side of the seat.

13. A highchair according to Claim 12 wherein the tray is carried by a tubular frame that is pivoted to the mounts.

14. A highchair according to any one of Claims 1 to 13 wherein the front leg-support of the elongate member splays out to form foot projections for floor-contact.